



Provedení:	II 2GD Ex e tD II T6 T85°C IP65/66
Teplota okolí*:	-60°C až +90°C
Materiál skříně:	X.X0 – AL slitina X.X1 – polyester X.X2 – nerez ocel
Svorcky:	2,5 až 300 mm ²
Vývodky:	viz katalogové listy vývodek
U _n :	500V, 690V, 750V, 1000V

* Jedná se o maximální rozsah.

PŘEHLED NEJPOUŽÍVANĚJŠÍCH ROZMĚROVÝCH TYPŮ

AL TLAK. ODLITEK	
Typ	Rozměry [mm]
X09X0	64 × 58 × 34
X10X0	64 × 98 × 34
X11X0	64 × 150 × 34
X16X0	80 × 75 × 57
X17X0	80 × 125 × 57
X18X0	80 × 175 × 57
X19X0	80 × 250 × 57
X21X0	120 × 122 × 80
X22X0	120 × 220 × 80
X23X0	120 × 220 × 90
X24X0	122 × 360 × 80
X25X0	160 × 160 × 90
X26X0	160 × 260 × 90
X27X0	160 × 360 × 90
X28X0	160 × 560 × 90
X29X0	230 × 200 × 110
X31X0	230 × 280 × 110
X32X0	230 × 330 × 110
X33X0	230 × 400 × 110
X35X0	230 × 600 × 110
X42X0	310 × 400 × 110
X43X0	310 × 600 × 110
X46X0	100 × 100 × 80
X47X0	100 × 160 × 80
X48X0	100 × 200 × 80
X49X0	120 × 122 × 90
X50X0	140 × 140 × 90
X51X0	140 × 200 × 90
X52X0	180 × 180 × 100
X53X0	180 × 280 × 100
X54X0	100 × 230 × 110
X55X0	230 × 200 × 180
X56X0	230 × 330 × 180
X57X0	230 × 400 × 224
X58X0	310 × 400 × 180
X59X0	310 × 400 × 226
X60X0	310 × 600 × 180
X70X0	600 × 600 × 200

POLYESTER	
Typ	Rozměry [mm]
X12X1	75 × 80 × 55
X13X1	75 × 110 × 55
X14X1	75 × 160 × 55
X15X1	75 × 190 × 55
X20X1	120 × 122 × 90
X23X1	120 × 220 × 90
X25X1	160 × 160 × 90
X26X1	160 × 260 × 90
X27X1	160 × 360 × 90
X28X1	160 × 560 × 90
X37X1	250 × 255 × 120
X38X1	250 × 255 × 160
X39X1	250 × 400 × 120
X40X1	250 × 400 × 160
X44X1	360 × 360 × 90
X45X1	405 × 400 × 120
X71X1	250 × 600 × 120
X72X1	80 × 75 × 75
X73X1	110 × 75 × 75
X74X1	160 × 75 × 75
X75X1	190 × 75 × 75
X80X1	400 × 405 × 165
X365X1	400 × 600 × 250

NEREZ	
Typ	Rozměry [mm]
X05X2	302 × 402 × 188
X06X2	pr. 133 × 80
X320X2	150 × 150 × 90
X321X2	200 × 150 × 90
X322X2	200 × 200 × 90
X323X2	300 × 150 × 90
X324X2	300 × 200 × 90
X325X2	300 × 300 × 90
X326X2	300 × 400 × 90
X327X2	400 × 200 × 90
X328X2	400 × 400 × 90
X329X2	560 × 400 × 90
X330X2	300 × 200 × 150
X331X2	300 × 300 × 150
X332X2	300 × 400 × 150
X333X2	400 × 200 × 150
X334X2	400 × 400 × 150
X335X2	560 × 400 × 150
X340X2	300 × 400 × 190
X341X2	400 × 400 × 190
X342X2	560 × 400 × 190
X343X2	800 × 400 × 190
X344X2	500 × 300 × 150
X345X2	500 × 400 × 150
X346X2	330 × 200 × 150
X347X2	330 × 300 × 150
X349X2	400 × 300 × 90
X357X2	400 × 300 × 150
X397X2	400 × 560 × 90
X398X2	400 × 560 × 150
X407X2	400 × 300 × 190
X408X2	330 × 200 × 190
X409X2	330 × 300 × 190
X410X2	400 × 560 × 190
X411X2	400 × 800 × 190
X412X2	500 × 300 × 190
X413X2	500 × 400 × 190

NEREZ	
Typ	Rozměry [mm]
X414X2	360 × 200 × 150
X415X2	360 × 300 × 150
X416X2	360 × 200 × 190
X417X2	360 × 300 × 190
X430X2	100 × 100 × 61
X431X2	150 × 100 × 61
X432X2	150 × 150 × 81
X433X2	200 × 100 × 61
X434X2	200 × 200 × 81
X435X2	200 × 200 × 121
X436X2	300 × 150 × 81
X437X2	300 × 200 × 81
X438X2	300 × 200 × 121
X439X2	300 × 300 × 121
X440X2	300 × 300 × 161
X441X2	380 × 380 × 161
X442X2	400 × 150 × 81
X443X2	400 × 200 × 121
X444X2	400 × 300 × 161
X445X2	500 × 300 × 161
X446X2	500 × 400 × 161
X460X2	200 × 250 × 97
X461X2	200 × 250 × 157
X462X2	350 × 250 × 97
X463X2	300 × 300 × 167
X464X2	380 × 380 × 167
X465X2	380 × 380 × 217
X466X2	500 × 300 × 167
X467X2	600 × 300 × 167
X468X2	600 × 380 × 217

Velikost skříně je dána požadovaným technickým zadáním (počet svorek, vývodek, napětí, proud). Na základě těchto údajů Vám navrheme optimální řešení. Kontaktujte naše oddělení OTS – e-mail: obchod@generi.cz.