LIMIT SWITCHES TYPE XCW....	
Type of protection:	**II 2GD EEx d IIC T6 IP66/67 T85°C**
Material:	Zinc-aluminium alloy
Description:	Limit switch with fixed 5-wire cable, each wire 0,75 mm², outside cable diameter 7 mm, delivered in the following lengths 1m, 2m, 5m 10m

Order No.		**Description**	**Contact function**	**closed / open**	
Fixed on body	**Fixed on head**				
XCW–A110	**XCW–F110**	Steel end plunger	BK black, BN brown, GN green, YW yellow, BK black, BU blue	1,5 — 0 1 5 mm	
XCW–A102	**XCW–F102**	Steel roller plunger for lateral cam approach		2,6(A) — 0 1 5 mm	
XCW–A103	**XCW–F103**	Steel roller plunger for traverse cam approach		2,6(A) — 0 1 5 mm	
XCW–A115	**XCW–F115**	Thermoplastic roller lever, rotary operation		1,5 — 0 1 5 mm	
Roller lever (accessories – assembled by the client)					
XCW–Z24		Roller lever		10(A) — 0 8,75	

LIMIT SWITCHES TYPE XC8...	
Type of protection:	**II 2GD EEx d IIC T6 IP65/66 T85°C**
Material:	Cast-iron
Description:	Limit switch is fastened by M20 (Nickel platted brass) cable gland and it is possible to connect both armoured and unarmoured cables, sealing ring for ranges from Ø 3 mm – Ø 15 mm.

Order No.		**Description**	**Contact function**	**closed / open**	
For non narmoured cable with clamping module	**For armoured cable**				
XC8–JC161P11 I C	**XC8–JC161P14 I**	Steel plunger		1,6 — 0 1,1 5 mm	
XC8–JC162P11 I C	**XC8–JC162P14 I**	Roller plunger		1,6 — 0 1,1 5 mm	
XC8–JC163P11 I C	**XC8–JC163P14 I**	Side plunger		2,7 — 0 2,1 5 mm	
XC8–TA1P11 I C	**XC8–TA1P14 I**	Heavy duty roller plunger		4 (A) — 0 3,4 mm	
XC8–JC10111P11 I C Actuation from left and right	**XC8–JC10111P14 I** Actuation from left and right	Delrin roller lever	11 13 / 12 14	14° — 0 8° 75°	
XC8–JC10511P11 I C Actuation from left and right	**XC8–JC10511P14 I** Actuation from left and right				
XC8–JC10131P11 I C Actuation from left and right	**XC8–JC10131P14 I** Actuation from left and right	Variable length Delrin roller plunger		14° — 0 8° 75°	
XC8–JC10531P11 I C Actuation from left and right	**XC8–JC10531P14 I** Actuation from left and right				
XC8–JC10151P11 I C Actuation from left and right	**XC8–JC10151P14 I** Actuation from left and right	Steel rod □3mm length 125 mm		14° — 0 8° 75°	
XC8–JC10551P11 I C Actuation from left and right	**XC8–JC10551P14 I** Actuation from left and right				

Further information available on request at **obchod@generi.cz**.