


<b>Type of protection:</b>	Ex II 2GD Ex d IIC EEx e II IP66, IP67
<b>Material:</b>	Nickel plated brass


Type 501/421 – for unarmoured cables	
Order No.	Ø cable [mm]
501/421/2K/M16 B.N.P.	3 – 8
501/421/OS/M20 B.N.P.	3 – 8
501/421/O/M20 B.N.P.	7,5 – 11,9
501/421/A/M20 B.N.P.	11 – 14,3
501/421/B/M25 B.N.P.	13 – 20,2
501/421/C/M32 B.N.P.	19 – 26,5
501/421/C2/M40 B.N.P.	25 – 32,5
501/421/D/M50 B.N.P.	31,5 – 44,4/42,3
501/421/E/M63 B.N.P.	42,5 – 56,3/54,3
501/421/F/M75 B.N.P.	54,5 – 68,2/65,3
501/421/G/M80 B.N.P.	67 – 73
501/421/H/M90 B.N.P.	67 – 77,6

Type 501/423 – for unarmoured cables	
Order No.	Ø cable [mm]
501/423/OS/M20 B.N.P.	3 – 8
501/423/O/M20 B.N.P.	7,5 – 11,9
501/423/A/M20 B.N.P.	11 – 14,3
501/423/B/M25 B.N.P.	13 – 20,2
501/423/C/M32 B.N.P.	19 – 26,5
501/423/C2/M40 B.N.P.	25 – 32,5
501/423/D/M50 B.N.P.	31,5 – 44,4/42,3
501/423/E/M63 B.N.P.	42,5 – 56,3/54,3
501/423/F/M75 B.N.P.	54,5 – 68,2/65,3


Type ICG 623 – Sealing for unarmoured cables	
Order No.	Ø cable [mm]
ICG 623/OS/M20 B.N.P.	3 – 8
ICG 623/O/M20 B.N.P.	7,5 – 11,9
ICG 623/A/M20 B.N.P.	11 – 14,3
ICG 623/B/M25 B.N.P.	13 – 20,2
ICG 623/C/M32 B.N.P.	19 – 26,5
ICG 623/C2/M40 B.N.P.	25 – 32,5
ICG 623/D/M50 B.N.P.	31,5 – 44,4
ICG 623/E/M63 B.N.P.	42,5 – 56,3
ICG 623/F/M75 B.N.P.	54,5 – 68,2



Type 501/421




Type 501/423



Type ICG 623



Type 501/453/UNIV



Type 501/453/RAC

ACCESSORIES AVAILABLE



Plugs 475 and 477 Ex d



Plugs 387 Ex e



Earth tag



Nut



Nylon sealing washer



Fibre sealing washer



Stainless steel serrated washer

Type 501/453/UNIV – for armoured cables					
Order No.	cable in Ø [mm]	cable out Ø [mm]	Order No.	cable in Ø [mm]	cable out Ø [mm]
501/453/UNIV/OS/M20 B.N.P.	3 – 8,1	5,5 – 12	501/453/UNIV/D/M50 B.N.P.	28,9 – 44,4/42,3	36 – 52,6
501/453/UNIV/O/M20 B.N.P.	6,5 – 11,9	9,5 – 16	501/453/UNIV/E/M63 B.N.P.	39,9 – 56,3/54,3	46 – 65,3
501/453/UNIV/A/M20 B.N.P.	8,4 – 14,3	12,5 – 20,5	501/453/UNIV/F/M75 B.N.P.	50,5 – 68,2/65,3	57 – 78
501/453/UNIV/B/M25 B.N.P.	11,1 – 20,2	16,9 – 26	501/453/UNIV/G/M80 B.N.P.	67 – 73	75 – 89,5
501/453/UNIV/C/M32 B.N.P.	17,6 – 26,5	22 – 33	501/453/UNIV/H/M90 B.N.P.	67 – 77,6	75 – 89,5
501/453/UNIV/C2/M40 B.N.P.	23,1 – 32,5	28 – 41			

Type 501/453/RAC – for armoured cables					
Order No.	cable in Ø [mm]	cable out Ø [mm]	Order No.	cable in Ø [mm]	cable out Ø [mm]
501/453/RAC/OS/M20 B.N.P.	3 – 8	5,5 – 12	501/453/RAC/D/M50 B.N.P.	31,5 – 44,4/42,3	36 – 52,6
501/453/RAC/O/M20 B.N.P.	7,5 – 11,9	9,5 – 16	501/453/RAC/E/M63 B.N.P.	42,5 – 56,3/54,3	46 – 65,3
501/453/RAC/A/M20 B.N.P.	11 – 14,3	12,5 – 20,5	501/453/RAC/F/M75 B.N.P.	54,5 – 68,2/65,3	57 – 78
501/453/RAC/B/M25 B.N.P.	13 – 20,2	16,9 – 26	501/453/RAC/G/M80 B.N.P.	67 – 73	75 – 89,5
501/453/RAC/C/M32 B.N.P.	19 – 26,5	22 – 33	501/453/RAC/H/M90 B.N.P.	67 – 77,6	75 – 89,5
501/453/RAC/C2/M40 B.N.P.	25 – 32,5	28 – 41			

Other modifications and technical data on brass cable glands available on request at [obchod@generi.cz](mailto:obchod@generi.cz).