


X12X1 0S23

POLYESTER BOXES TYPE X12X1	
<b>Type of protection</b>	Ⓜ II 2G Ex eb IIC T6 Gb Ⓜ II 2D Ex tb IIIC T85°C Db
Ingress protection	IP 66
Ambient temperature	-35 °C ≤ Ta ≤ +40 °C
Rated voltage	550 V
Rated loading	1,5 mm <sup>2</sup> : 13 A; 2,5 mm <sup>2</sup> : 16 A
Dimensions (w × h × d)	80 × 75 × 55 mm
Mounting holes / spacings	4 × ø5 / 68 × 45 mm

Terminals	Cable glands	Weight	Order number
spring-cage 4 pcs 4 × 2.5 mm <sup>2</sup> grey 1 pc 4 × 2.5 mm <sup>2</sup> g/y	4 pcs M20 (ø7 – ø12) mm 2 pcs plug M20 (loose part)	0,3 kg	<b>X12X1 0S23</b>




X20X1 0S01


POLYESTER BOXES TYPE X20X1	
<b>Type of protection</b>	Ⓜ II 2G Ex eb IIC T6 Gb Ⓜ II 2D Ex tb IIIC T85°C Db
Ingress protection	IP 66
Ambient temperature	-40 °C ≤ Ta ≤ +40 °C
Rated voltage	550 V
Rated loading	1,5 mm <sup>2</sup> : 10 A; 2,5 mm <sup>2</sup> : 16 A, 4 mm <sup>2</sup> : 20 A; 6 mm <sup>2</sup> : 25 A
Dimensions (w × h × d)	122 × 120 × 90 mm
Mounting holes / spacings	4 × ø6,6 / 106 × 82 mm

Terminals – spring-cage	Cable glands	Weight	Order number
4 pcs 3 × 2.5/4 mm <sup>2</sup> grey 1 pc PE rail	4 pcs M25 (ø7 – ø17) mm 2 pcs plug M25 (loose part)	1,0 kg	<b>X20X1 0S01</b>
8 pcs 2 × 2.5/4 mm <sup>2</sup> grey * 1 pc PE rail	4 pcs M25 (ø7 – ø17) mm 2 pcs plug M25 (loose part)	1,0 kg	<b>X20X1 0S02</b>
4 pcs 2 × 4/6 mm <sup>2</sup> grey 1 pc PE rail	3 pcs M25 (ø10 – ø17) mm 1 pc plug M25 (loose part)	1,0 kg	<b>X20X1 0S03</b>
8 pcs 2 × 4/6 mm <sup>2</sup> grey * 1 pc PE rail	3 pcs M25 (ø10 – ø17) mm 1 pc plug M25 (loose part)	1,1 kg	<b>X20X1 0S04</b>
8 pcs 2 × 4/6 mm <sup>2</sup> grey * 1 pc PE rail	4 pcs M25 (ø10 – ø17) mm 1 pc plug M25 (loose part)	1,1 kg	<b>X20X1 0S05</b>


\* The terminals are connected to the four pairs.




X20X1 0S02



X20X1 0S03



X20X1 0S04



X20X1 0S05

Other variants to order.

Detailed technical data on demand – e-mail: obchod@generi.cz.